FUJITSU

DATA SHEET

STYLISTIC ST6012

Issue: **July 2009**

The ideal mobile solution for indoors and outdoors

STYLISTIC ST6012

The STYLISTIC ST6012 is the perfect companion. The device weighs only 1.6kg, is very easy to carry yet robust. It was specially developed for use when standing or walking.
The transmissive 30.7 cm (12.1-inch) TFT WXGA display offers the best image quality. Support for pen-based functions helps you carry out your work anywhere and to present it convincingly.
A further advantage is the battery runtime which enables you to work for a long period. Take a good look at the new housing. As well as being lightweight, the housing provides additional protection against damp or dust.

Unlimited mobility

Small, lightweight, very easy to carry, created for optimized mobility.

- A4 format, only 1.6 kg, personalized keys for easy and fast access to your applications

Highest security

Perfect data protection against non-authorized access.

- Computrace® enabled BIOS, integrated SmartCard Reader, Fingerprint sensor & TPM module

Extreme productivity

Non-stop working, without any loss of speed

- Intel® Core™2 Duo processor SU9400 (ULV)

Connectivity wherever you are

Unlimited connectivity - indoors and outdoors.

- Optional integrated high-speed UMTS, WLAN and Bluetooth

SIERRA WIRELESS EMPOWERED

ENERGY STAR

Green IT

BEST CONNECTIVITY

SYSTEM GUARDS

ULTIMATE SECURITY

PEN BASED COMPUTING

LIGHT WEIGHT

CONFCAM

TWINLOAD

Components

Memory modules	2 GB (1 module(s) with 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
	1 GB (1 module(s) with 1 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
Hard disk drives (internal)	320 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	128 GB SSD SATA, 2.5-inch S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software

Battery		
Battery type	Li-Ion battery 6-cell	Li-Ion battery 9-cell
Battery power	56.16 Wh	84.24 Wh
Battery capacity	5.200 mAh	7.800 mAh
Runtime 1st battery	Up to 5:30 h	Up to 9:00 h
Battery features	Dynamic charge supported (rapid charge)	
Benchmark	Mobile Mark 2005	
Battery notes	Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.	

WLAN (optional)	Atheros Minicard b/g 802.11 b/g
	Intel® Wireless WiFi Link 5300 AGN 11/13ch
UMTS/HSUPA (optional)	Sierra Wireless MC8790 (downlink 7.2 MBit/s, uplink 2.0 MBit/s)
Bluetooth (optional)	Bluetooth 2.1

Base unit	**STYLISTIC ST6012**

General system information	
Processor	Intel® Core™2 Duo processor LV SU9400 (1.4 GHz), 3 MB, 800 MHz
Chipset	Intel® GS45, ICH9-M
BIOS features	BIOS Flash EPROM BIOS based on Phoenix TrustedCore Notebook
Memory slots	2 DIMM
Turbo memory	Optional 4 GB
Supported capacity RAM (max.)	4 GB
Memory notes	8 GB - with future memory modules.

Interfaces	
Memory card slots	1 (SD)
PC Card slot (Type I/II)	1
SmartCard slot	1
SIM card slot	1
USB 2.0 total	2
VGA	1
Ethernet (RJ-45)	1
Audio: line-in / microphone	1
Audio: line-out / headphone	1
Internal microphones	2
Docking connector for Port Replicator	1
Kensington Lock support	1

Wired communication	
LAN	Built-in 10/100/1000 MBit/s Intel® 82567LF

Wireless technologies	
Antennas	3 Dual band WLAN antennas, 2 UMTS antennas, 1 Bluetooth
WLAN notes	Import and usage according to country-specific regulations.
UMTS	option

Keyboard and pointing devices	
	Fingerprint sensor Launch keys Status LED Application buttons Tablet Pen Digitizer Fingerprint sensor scroll

Multimedia	
Audio type	On board
Audio codec	Realtek ALC269
Audio features	Mono speaker
Camera	Optional: Built-in webcam, 1.3 megapixel

Graphics	
Display	30.7 cm (12.1-inch) TFT active digitizer 1280 x 800 pixel (WXGA) non-glare display
Display notes	Wide-View High-Bright LED WXGA Display (for enhanced outdoor viewing)
Max. resolution external display	1920 x 1200 / true color / 85 Hz
Graphics brand name	Mobile Intel® GMA 4500M HD
Graphic features	DualView (Windows XP & Windows Vista)

Power supply	
AC adapter	16 V / 60 W (3.75 A)
Rated voltage range	100 - 240 V (AC Input)
Rated frequency range	50 - 60 Hz

Power consumption	
Power consumption note	see white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=405a7569-10c7-4be5-91ba-a51472338614

Dimensions / Weight / Environmental	
Dimension (W x D x H)	325 x 220 x 23.8 - 31.7 mm
Weight	1.6 kg
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35°C
Operating relative humidity	20 - 80 %

Operating system	
Operating system optional preinstalled	TwinLoad Microsoft® Windows® XP Tablet PC Edition 2005 (DVD) Microsoft® Windows Vista® Business 32bit
Operating system compatible	Microsoft® Windows® XP Tablet PC Edition 2005
Operating system notes	Driver support for Microsoft Windows XP

Additional Software	
Additional software (preinstalled)	Adobe Acrobat Reader Application Panel Drivers & Utilities DVD (DUDVD) Microsoft® Office Ready (Trial) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Toshiba Bluetooth Stack EasyGuide online user documentation Tablet Button Utility
Additional software (optional)	Windows Vista® recovery media Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS)

Additional Software	
Additional software (included as a CD/DVD)	SmartCase Logon+

Manageability	
Manageability features	DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional)
Manageability type	DeskView 10.x client management including:
DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html

Security	
Physical security	Kensington Lock support
System security	Computrace® enabled BIOS Symantec Norton Internet Security (90 day test version) Write protect option for the Flash EPROM Control of all USB interfaces
User security	Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support Hard disk password SystemLock 2 BIOS SmartCard Security SmartCase Logon+ incl. Fingerprint software User and supervisor BIOS password

Compliance	
Model	ST60xx
Europe	CE Nordic Swan in progress
USA/Canada	FCC Class B (depending on wireless configuration)
Global	WiFi certified ENERGY STAR® 4.0
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Docking devices (optional)	
	Tablet Dock
DC-in	1
Audio: line-out / headphone	1
USB 2.0 total	3
VGA	1
Ethernet (RJ-45)	10/100/GB LAN
Kensington Lock support	2
Drive name	DVD Super Multi

Warranty	
Standard Warranty	2 years
Service level	Collect & Return Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	3 years, Collect and Return Service, where available: Executive On-site Service
Spare Parts availability	5 years
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions July 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com